# WaterRidge<sup>®</sup>

### WaterRidge® One Piece 1.6 gpf( 6.0 Lpf)/1.1 gpf(4.1 Lpf) ADA Elongated Toilet

### Features: C22148C

- Vitreous China
- 12" Rough-In
- $3^{\prime\prime}$  canister flush valve for faster water flow and flushing power
- Extra-large Dual fed siphon jets for high power bowl clearing
- Chrome-plated top-mount button flush actuator
- 100% glazed, 2" trapway for clog-free waste removal
- Slow Close and Quick-release seat included for fast and easy cleaning
- Wax ring, braided hose, floor bolts and bolts caps included
- MaP 1000 g



FINISHED WALL	$ \begin{array}{c} 277 \frac{5}{6}'' \\ 700mm \\ 190mm \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1$
<sup>7</sup> /s" 22mm <sup>3</sup> /s"N.P.T SUPPLY <sup>4</sup> <sup>8</sup> ″ <sup>203</sup> mm <sup>4</sup> <sup>152</sup> mm	28 '/s" 28 '/s" 714mm 16 '/z" 203mm 203



NOTES: All dimensions are in inches and millimeter. Illustrations may not be drawn to scale.

IMPORTANT:

Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME standard A112.19.2/CSA B45.1 THIS FIXTURE QUALIFIES ACCORDING TO ASME TEST PROCEDURES AS EITHER AS HIGH EFFICIENCY WATER CLOSET WITH AN AVERAGE CONSUMPTION OF 1.1 gpf (4.1 Lpf), OR A LOW CONSUMPTION WATER CLOSET WITH AN AVERAGE CONSUMPTION OF 1.6 gpf (6.0 Lpf). WATER CLOSET CONSUMPTION IS DETERMINED BY THE TANK.

## Technical Information:

Configuration	One Piece ADA Elongated Toilet
Water per Flush	1.6 gpf(6.0 Lpf)/1.1 gpf(4.1 Lpf)
Rough-In	12″
Height	28 <sup>1</sup> /8″
Width	15 <sup>3</sup> /8″
Depth	27 5/8″
Trapway	2"
Large Water Surface	8 <sup>11</sup> /16" x 6 <sup>5</sup> /16"
Shipping weight	99.6 lbs

Accessories: (To be purchased separately) N/A

### Available Colors:

• White

#### Warranty:

• 5 YEARS limited warranty

Because we are committed to continual product improvement, specifications are subject to change without notice. © 2020 Globe Union Industrial Corp. All rights reserved Globeunion.com